



F 140

Forward vibratory plate



News 2019,
new ergonomic and de-vibrated handle

For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable, which means lower operating and maintenance costs.

- The Swepac F 140 is the ideal high-performance all-round machine.
- Ergonomic de-vibrated handle with reduced vibration levels
- The compact design also makes it suitable in trenches, and with a Vulkollan® plate (accessory) attached to the base, it can compact paved areas efficiently for an even surface.
- Integrated transport wheels can be used to move the machine short distances between jobs.
- The chassis and protection frame are hot-dip galvanized providing a superior corrosion protection and maintenance-free life.

TECHNICAL DATA SWE PAC F 140

Weight, net	141 kg
Base plate, width x length	460 x 610 mm
Height, max / min	1090 / 870 mm
Length, max / min	1050 / 625 mm
Engine	Honda GX 160
Fuel tank capacity	3.6 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	3.6 kW (4.8 hp)
Centrifugal force	19 kN
Frequency	88 Hz
Working speed	0 - 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	2.8 m/s ²
Guaranteed sound-power level, L _{WA}	105 dB(A)
Sound pressure level (at operator's ear), OP	90 dB(A)

Part number

201090	F 140 with Honda petrol engine
--------	--------------------------------

Accessories

201047	Vulkollan plate complete
--------	--------------------------

Swepac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swepac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, www.swepac.com. We reserve the right to make changes in technical specifications without prior notice.

Swepac AB
Blockvägen 3 | SE-341 32 Ljungby | Sweden
Tel +46 (0)372-156 00 | www.swepac.com

swepac