

FB 160

REVERSIBLE VIBRATORY PLATE



For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable meaning lower operating and maintenance costs.

- The Swepac FB 160 is a high-performance petrol powered reversible compactor.
- The FB 160 is fast with a superior traction capability and is equipped with a fully variable speed control.

- The chassis, protection frame and handle are hot-dip galvanized providing a superior corrosion protection and maintenance-free life.
- The FB 160 also has a sturdy protective frame, with a strong lifting hook providing effective protection against external damage.
- The Hardox® wear plate ensures a long service life.
- The compact design makes it suitable in trenches and other areas with limited space.
 With a Vulkollan® plate (accessory) attached to the base, it compacts paved areas efficiently for an even surface.
- The machine is designed to be highly ergonomic and has a spring-mounted control handle for low handle vibrations.
- The open design offers easy access for regular service and maintenace resulting in high utilization and low operating and maintenance costs.

TECHNICAL DATA	– SWEPAC FB 160
Unleaded or alkylate petrol	160 / 164.3 kg
Base plate, width x length	450/550 x 720 mm
Height, max / min	1180 / 1000 mm
Length, max / min	1440 / 800 mm
Engine	Honda GX 200
Fuel tank capacity	3.1 liter
Fuel	Unleaded or alkylate petrol
Engine output, max	4.3 kW (5.8 hp)
Centrifugal force	32 kN
Frequency	83 Hz
Working speed	0-25 m/min

Hand/arm vibrations HAV according to ISO 5349 on gravel surface	2.5 m/s ²
Guaranteed sound-power level, LWA	105 dB(A)
Sound pressure level (at operator's ear), OP	91 dB(A)

PART NUMBE	ER
304000	FB 160 base plate width 450 mm
304060	FB 160 base plate width 550 mm

ACCESSORIES	
303260	Vulkollan plate complete 550 mm
303277	Vulkollan plate complete 450 mm

FB160_2021-05_GB