



# FB 175

## Reversible vibratory plate

### For compaction of sand, gravel, rock fill and paving stones.

All our machine models are versatile and easy to operate. They are also durable and reliable meaning lower operating and maintenance costs.

- The Swepac FB 175 is a high-performance diesel-powered reversible compactor.
- Cyclone pre-cleaner air filter, improves dust filtering efficiency and lowers maintenance cost.
- The FB 175 is fast with a superior traction capability and is equipped with a fully variable speed control.
- The chassis, protection frame and handle are hot-dip galvanized providing a superior corrosion protection and maintenance-free life
- The FB 175 also has a sturdy protective frame, with a strong lifting hook providing effective protection against external damage.
- The Hardox® wear plate ensures a long service life.
- The compact design makes it suitable in trenches and other areas with limited space. With a Vulkollan® plate (accessory) attached to the base, it compacts paved areas efficiently for an even surface.
- The machine is designed to be highly ergonomic and has a spring-mounted control handle for low handle vibrations.
- The open design offers easy access for regular service and maintenance resulting in high utilization and low operating and maintenance costs.

Swepac is Sweden's leading manufacturer of soil compactors. The company has a wide range of products, with different motor options and a variety of sizes for every application. Swepac is certified for quality and environmental management under ISO 9001 and 14001, and our machines are Eurotest-certified by SMP Swedish Machinery Testing Institute. You will find detailed information about the company and our products on our website, [www.swepac.com](http://www.swepac.com). We reserve the right to make changes in technical specifications without prior notice.

Swepac AB  
Blockvägen 3 | SE-341 32 Ljungby | Sweden  
Tel +46 (0)372-156 00 | [www.swepac.com](http://www.swepac.com)

Non stage-5 engine

#### TECHNICAL DATA SWEPAC FB 175

Weight, net	165/ 169.3 kg
Base plate, width x length	450 / 550 x 720 mm
Height, max	1180 mm
Length, max	1440 mm
Engine	Yanmar L 48
Fuel tank capacity	3 liter
Fuel	Diesel
Engine output, max	3.1 kW (4.0 hp)
Centrifugal force	32 kN
Frequency	82 Hz
Working speed	0 - 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	2.5 m/s <sup>2</sup>
Guaranteed sound-power level, L <sub>WA</sub>	108 dB(A)
Sound pressure level (at operator's ear), OP	92 dB(A)

#### Part number

304075	FB 175 base plate width 450 mm
304085	FB 175 base plate width 550 mm

#### Accessories

303260	Vulkollan plate complete 450 mm
303139	Vulkollan plate complete 550 mm