

FBM

Finishing beam,
manual



Lightweight and smooth aluminium finishing beam

- Unique profile that gives the floor a precise level
- Flows easily and is easy to manoeuvre
- A 30 mm aluminium handle rod with a plastic coating that protects the aluminium surface against concrete splashes, which also insulates against cold in the winter and heat in summer
- As standard, the handle rod is 2 or 3 meters long. Due to a simple and smooth conductor joint, it is easy to double the handle rod's length if extra long handles are desired
- The parts are easy to assemble and disassemble
- The beam profile can have different widths, and if needed, can be easily cut down to shorter dimensions

TECHNICAL DATA

SWEPAC FBM

Profile

Weight (kg/length)	3,6 / 4,4 / 5,7 / 6,3
Length, standard (m)	1,2 / 1,5 / 2 / 2,2
Width (mm)	155 mm

Handle rod (shaft)

Weight (kg/m) (0,5kg/ M)	1 / 1,5 / 2
Length (m)	2 / 3 / 4 / optional
Split (m)	Two optional lengths

Swepac offers a wide range of models with many different engine versions and sizes suitable for any application. Swepac is quality and environment certified in accordance with ISO 9001 and 14001 and the machines are certified to the Euro Test standard by the Swedish Machine Testing Authority. Information about the company and our products can be found on our home page at: www.swepac.com. We retain the right to change the technical specifications without any prior notification.

Swepac AB
Blockvägen 3 | SE-341 32 Ljungby | Sweden
Tel +46 (0)372-156 00 | www.swepac.com

SWEPAC