

FB 500

REVERSIBLE VIBRATORY PLATE



For compaction of sand, gravel, rock fill and soil with high clay content.

All our machine models are versatile and easy to operate. They are also durable and reliable meaning lower operating and maintenance costs.

• The Swepac FB 500 is a heavyweight compact diesel-powered machine with high compaction capacity. Despite its weight, it is well balanced and easy to maneuver.

- The FB 500 is V-belt driven offering superior traction capability and is equipped with a fully variable speed control.
- The chassis, protection frame and handle are hot-dip galvanized providing a superior corrosion protection and maintenance-free
- The FB 500 also has a sturdy protective frame, with a strong lifting hook providing effective protection against external damage.
- The Hardox® wear plate ensures a long service life.
- The machine is designed to be highly ergonomic and has a spring-mounted control handle for low handle vibrations and can be equipped with a heating element in the grip as an option.
- The open design offers easy access for regular service and maintenace.

TECHNICAL DATA – SWEPAC FB 500	
Weight, net	490 kg
Base plate, width x length	700 x 1080 mm
Height, max / min	1235 / 1050 mm
Length, max / min	1830 / 1180 mm
Engine	Hatz Supra 1D50Z
Fuel tank capacity	5.5 liter
Fuel	Diesel
Engine output, max	7.5 kW (10.1 hp)
Battery capacity	40 Ah
Generator output	180 W (15A)

Centrifugal force	66 kN
Frequency	72 Hz
Working speed	0 - ca 25 m/min
Hand/arm vibrations HAV according to ISO 5349 on gravel surface	2.6 m/s2
Guaranteed sound-power level, LwA	108 dB(A)
Sound pressure level (at operator's ear), OP	93 dB(A)

PART NUMBER	
307600	FB 500 with Hatz diesel engine

FB500_2021-05_GB